


PRODUCT DETAIL :




USAGE

Fry Reglet "F" Reveal Molding is used to form wall trim reveal where drywall terminates against sill, jamb, ceiling or other finish material in the same plane. Supports ceiling material.

GUIDE SPECIFICATION

Where indicated on drawings, Fry Reglet "F" Reveal Molding, as manufactured by Fry Reglet Corporation, shall be installed. Aluminum shall be extruded alloy 6063 T5, with chemical conversion coating, clear anodized or other specified finish. Refer to finish section.

INSTALLATION DETAIL : Cross Section



"F" REVEAL MOLDING SIZES

DIM. A REVEAL DEPTH	DIM. B REVEAL WIDTH		
		NON-VENTED	VENTED
1/2"	1/8"	DRMF-50-125	-
1/2"	1/4"	DRMF-50-25	-
1/2"	3/8"	DRMF-50-375	-
1/2"	1/2"	DRMF-50-50	DRMF-50-V-50
1/2"	5/8"	DRMF-50-625	DRMF-50-V-625
1/2"	3/4"	DRMF-50-75	DRMF-50-V-75
1/2"	1"	DRMF-50-100	DRMF-50-V-100
5/8"	3/8"	DRMF-625-375	-
5/8"	1/2"	DRMF-625-50	DRMF-625-V-50
5/8"	5/8"	DRMF-625-625	DRMF-625-V-625
5/8"	3/4"	DRMF-625-75	DRMF-625-V-75
5/8"	1"	DRMF-625-100	DRMF-625-V-100
5/8"	1 1/2"	DRMF-625-150	DRMF-625-V-150
5/8"	2"	DRMF-625-200	DRMF-625-V-200
5/8"	3"	DRMF-625-300	DRMF-625-V-300

INSTALLATION DETAIL : ISO View

